

The 2nd AEGIS Symposium on Cyber Security
2023 - 2024 (Online)

Phoenix Domain Attack: Vulnerabilities in Domain Name Delegation and Revocation

[Published at NDSS '23]

Presenter: **Xiang Li**, Tsinghua University

August 2023



Xiang Li (理想)

➤ 5th-year Ph.D. Candidate

- ❑ Tsinghua University (NISL Lab), UCI (visiting scholar)
- ❑ Advisor(s): Prof. Qi Li and Haixin Duan

➤ Research Area and Publication

- ❑ Network scanning, IPv6 security, DNS security, vulnerability discovery, and fuzzing
- ❑ **Publications in total (12):** S&P ('24), NDSS ('23, '24), Security ('23a, '23b, '24), CCS ('23a, '23b), DSN ('21), VehicleSec ('23), SIGMETRICS ('23), IMC ('23)
- ❑ **Publications as the 1st author (5):** [S&P \('24\)](#), [NDSS \('23\)](#), [Security \('23\)](#), [CCS \('23\)](#), [DSN \('21\)](#)
- ❑ **Publications under review (5):** S&P (['24a](#), '24b), NDSS ('24a, '24b)
- ❑ **Industry Conferences:** IDS ('21, '22), DNS OARC (39, 40, 41), Black Hat (Asia '23, USA '23)
- ❑ **CNVD/CVE:** 109/70.

Phoenix Domain Attack: Vulnerable Links in Domain Name Delegation and Revocation

Presenter: **Xiang Li**, Tsinghua University

August 2023



Exploitation Impact



Even a domain expired or was removed,

**Attackers could still use it for free
with the Phoenix Domain Attack.**

Domain Name

➤ Domain name system (DNS)

- ❑ Entry point of many Internet activities
- ❑ Security guarantee of multiple application services
- ❑ Domain names are widely registered



Domain Name Abuse

➤ Also abused by criminal activities

- ❑ Botnet, phishing, malware distribution



bleepingcomputer.com



scmp.com



norton.com

Domain Name Abuse

- **Also abused by criminal activities**
 - ❑ Botnet, phishing, malware distribution
- **ICANN Domain abuse activity reporting (DAAR)**
 - ❑ In July 2023
 - ❑ Check 217M domain names within 1.1K gTLDs

**576K domains
showing security threats**

Domain Name Revocation

- **Fighting against malicious domain names**
- **Mechanism**
 - ☐ Domain name revocation
 - ☐ Operated by registries or registrars
 - ☐ Deleting or changing domain name registration (delegation)
- **Result**
 - ☐ Domains are no longer controlled by original registrants/attackers

Domain Name Revocation

➤ Domain name seizure activity

- ❑ Best security practice
- ❑ Widely adopted

Microsoft seizes Chinese dot-org to kill Nitol bot army

Takedown after infected new computers sold to victims

 [John Leyden](#)

Thu 13 Sep 2012 // 15:01 UTC

Microsoft has disrupted the emerging Nitol botnet - and more than 500 additional strains of malware - by taking control of a rogue dot-org website. The takedown is the latest in Microsoft's war against armies of hacker-controlled PCs.

theregister.com



intelligentciso.com

Question

How does domain name revocation work on domain name registration (delegation)?


It is the reverse process of **delegation**.

Domain Name Revocation


➤ Normal resolution

➤ Revocation


- ☐ Domain delisting
- ☐ Domain sinkholing



Normal resolution



Domain delisting



Domain sinkholing

Question



**Does domain name revocation
function as desired?**

No. **Ghost domain** broke this guarantee.

Ghost Domain

➤ Ghost domain attack

- ❑ Proposed in NDSS 2012 by our NISL lab
- ❑ Making revoked domain names still resolvable on resolvers



Takeaway

With ghost domain, even after revocation, malicious domains can still be resolvable.

Attackers can use it to evade **domain take-down** or **domain expiration**.

Ghost Domain


➤ Vulnerable software

- ❑ Not all software: BIND, PowerDNS, etc.

➤ Mitigation

- ❑ TTL field cannot be prolonged

DNS Vendor	Version	Vulnerable?
BIND	9.8.0-P4	Yes
DJB dnscache	1.05	Yes
Unbound	1.4.11	No
	1.4.7	Yes
PowerDNS	Recursor 3.3	Yes
MaraDNS	Deadwood-3.0.03	No
	Deadwood-2.3.05	No
Microsoft DNS	Windows Server 2008 R2	No
	Windows Server 2008	Yes



Question

10 years later, does domain name revocation work as desired after fixing ghost domain?

No. **Phoenix domain** still breaks this guarantee with a broader attack surface.

Phoenix Domain

➤ What is phoenix domain

- ☐ Proposed by our NISL lab too
- ☐ Published at NDSS 2023
- ☐ Also making revoked domain names still resolvable on resolvers
- ☐ Two new vulnerabilities in protocols or implementations
- ☐ Two variations (**T1** and **T2**)
- ☐ Affecting all DNS implementations


Question

**Why is domain name revocation
still vulnerable?**

We find that the entire attack surface
remains unclear now.

DNS Cache Operations


➤ Summary



DNS Cache Operations

➤ Summary

- ❑ Updating
- ❑ Insertion
- ❑ Searching



Question



How does Phoenix Domain work?

Two variations, two ways.

Phoenix Domain T1

➤ T1 attack


- ❑ Exploiting vulnerable cache insertion implementations
- ❑ Inserting new NS records **when the old is about to expire**



Phoenix Domain T1

➤ T1 attack



- ❑ Attack steps
- ❑ Cache expiration
- ❑ Cache deletion
- ❑ Cache insertion



Phoenix Domain T2

➤ T2 attack


- ❑ Exploiting vulnerable cache searching operations
- ❑ Inserting new NS records of subdomains



Phoenix Domain T2

➤ T2 attack

- ❑ Exploiting vulnerable cache searching operations
- ❑ Inserting **new NS records of subdomains**



Vulnerable Software

➤ Phoenix domain T1

- ❑ BIND9, Knot, Unbound, and Technitium

➤ Phoenix domain T2

- ❑ All tested 8 software are vulnerable (7 confirmed, 9 CVEs)

BIND 9

**KNOT
RESOLVER**

unbound

POWERDNS

**Microsoft
DNS**

MaraDNS

Simple DNS Plus

Technitium DNS Server

CVE-2022-30250 CVE-2022-30251
CVE-2022-30252 CVE-2022-30254
CVE-2022-30256 CVE-2022-30257
CVE-2022-30258 CVE-2022-30698
CVE-2022-30699

Vulnerable Public Resolvers

➤ Phoenix domain T1 and/or T2

- ❑ We test 41 public resolver vendors
- ❑ All resolvers are vulnerable to T1 and/or T2
- ❑ Such as Google, Cloudflare, Akamai, AdGuard, etc. (15 confirmed)



Vulnerable Open Resolvers

- Recursive resolver list
 - ❑ Through scanning, we collected 1.2M resolvers
 - ❑ 210k recursive resolvers are selected



Region	Number	%	ASN	Number	%
USA	43,034	20.5%	4837	9,825	4.7%
China	25,152	12.0%	4134	5,988	2.9%
Russia	22,802	10.9%	3462	5,864	2.8%
Japan	13,421	6.4%	4713	5,134	2.4%
France	12,801	6.1%	8866	4,884	2.3%
Turkey	8,389	4.0%	9121	4,779	2.3%
Brazil	7,128	3.4%	16276	4,355	2.1%
Sweden	7,026	3.3%	209	3,937	1.9%
Taiwan	6,869	3.3%	3215	3,735	1.8%
Ukraine	6,572	3.1%	12389	3,485	1.7%
Total 218 regions			Total 11,274 ASes		


Experiments for T2

➤ Short-term experiments

- ❑ Check how many labels are supported

- ❑ 89% are vulnerable


- ❑ After 100 rounds, 42% are vulnerable



Experiments for T2

➤ Long-term experiments


- ❑ Check how long phoenix domain can be alive
- ❑ After **one week**, **40%** are vulnerable
- ❑ After **one month**, **25%** are vulnerable



Experiments for T2

➤ Geolocation of vulnerable resolvers

☐ USA, Russia, and China



Mitigation

- 6 approaches
- Discussing with RFC editors
- For example,
- **M1**: when NS RRs expire, querying upstream for NS
- **M2**: trust NS from the parent more than the child
- **M3**: use small TTL values

Delegation Revalidation by DNS Resolvers
 draft-ietf-dnsop-ns-revalidation-03

Mitigation	T1	T2
M1: Re-validating delegation information	●	●
M2: Updating delegation data by parent-centric policies.	●	○
M3: Aligning the cache use-and-check operations	●	○
M4: Ignoring unsolicited DNS records	◐	◐
M5: Scrutinizing domain names with over many labels	○	◐
M6: Restricting the maximum cache TTL	○	◐

●: Fully valid. ◐: Partially valid. ○: Not valid.

Sound Bytes

- **The DNS RFCs and specifications are not clear to provide a deterministic definition for each operation, hence leaving a large attack window for ambiguous implementations.**
 - ❑ We should check the RFC's essential specifications.
- **The DNS implementations are not consistent across software, even for identical client queries.**
 - ❑ This inconsistency is likely to conceal possible risks, which should be thoroughly researched and evaluated.
- **The original DNS mechanism is insufficient to defend against several types of attacks.**
 - ❑ To improve it, we should propose new patches or redesign some structures.

Wrap-up

Thanks for listening!
Any question?

Xiang Li, Tsinghua University

x-l19@mails.tsinghua.edu.cn



Paper



Tool